

## Hydraulic Attachments

### SW SERIES COMPACTION WHEEL

Striker's Compaction Wheel works through trench fill to compact soil from the bottom to the top. Operators, experienced with the "feel" of the wheel in the trench, can determine if the appropriate compaction has been reached by the way the hydraulic controls of the machine handle the attachment.

#### *SW Series Features:*

- Constructed from durable, high quality steel
- Built to last with double tapered roller bearings
- No special hydraulic systems required
- Machine to machine versatility
- Easy five minute maintenance



Model Number	Description				Shipping Weight
<b>Skid Steer Loaders &amp; Mini-Excavators up to 11,500 lbs</b>					
SCW-4/6-ME	4" / 6" Width	Standard Bearings	1 Rim		775 lbs
SCW-12-ME	11" Width	Standard Bearings	2 Rims		600 lbs
SCW-18-ME	17" Width	Standard Bearings	3 Rims		750 lbs
SCW-24-ME	23" Width	Standard Bearings	3 Rims		775 lbs
SCW-36-ME	35" Width	Standard Bearings	4 Rims		1250 lbs
<b>Small Backhoe/Mini Excavator 11,500 lbs to 17,500 lbs</b>					
SCW-6-SBME	4" / 6" Width	Standard Bearings	1 Rim		875 lbs
SCW-12-SBME	11" Width	Standard Bearings	2 Rims		750 lbs
SCW-18-SBME	17" Width	Standard Bearings	3 Rims		1050 lbs
SCW-24-SBME	23" Width	Standard Bearings	3 Rims		1150 lbs
SCW-36-SBME	35" Width	Standard Bearings	4 Rims		1650 lbs
<b>Large Backhoe/Small Excavator 17,500 lbs to 27,500 lbs</b>					
SCW-12-LBSE	11" Width	Standard Bearings	2 Rims		975 lbs
SCW-18-LBSE	17" Width	Standard Bearings	3 Rims		1175 lbs
SCW-24-LBSE	23" Width	Standard Bearings	3 Rims		1275 lbs
SCW-36-LBSE	35" Width	Standard Bearings	4 Rims		1650 lbs
<b>Small/Medium Excavator 27,000 lbs to 50,000 lbs</b>					
SCW-14-SME	13" Width	Standard Bearings	2 Rims		1725 lbs
SCW-18-SME	17" Width	Standard Bearings	3 Rims		2125 lbs
SCW-24-SME	23" Width	Standard Bearings	3 Rims		2270 lbs
SCW-36-SME	35" Width	Standard Bearings	4 Rims		2350 lbs
SCW-48-SME	47" Width	Standard Bearings	5 Rims		3250 lbs
<b>Medium Excavator 50,000 lbs to 75,000 lbs</b>					
SCW-24-MDE	23" Width	Standard Bearings	3 Rims		3300 lbs
SCW-36-MDE	35" Width	Standard Bearings	4 Rims		3700 lbs
SCW-48-MDE	47" Width	Standard Bearings	5 Rims		4650 lbs
SCW-60-MDE	59" Width	Standard Bearings	6 Rims		5220 lbs
<b>Large Excavator 75,000 lbs to 115,000 lbs</b>					
SCW-24-LGE	23" Width	Standard Bearings	3 Rims		3700 lbs
SCW-36-LGE	35" Width	Standard Bearings	4 Rims		4150 lbs
SCW-48-LGE	47" Width	Standard Bearings	5 Rims		5140 lbs
SCW-60-LGE	59" Width	Standard Bearings	6 Rims		5940 lbs

Distributor

**TOKU America Inc.**

3900 Ben Hur Avenue, Unit 3  
 Willoughby, Ohio 44094  
 t. 440.954.9923  
 f. 440.954.9929

[www.toku-america.com](http://www.toku-america.com)