

DC CI

0490592 0501735

T&H DRUM CUTTER

Breaking innovation, Getting more Benefits.

www.tnhkorea.co.kr



Series



T&H CORPORATION DRUM CUTTERS

• Hydraulic Drum Cutter TDC series

The drum cutters in the "TDC series" are particularly for working in the construction industry, cutting channels and tunnels, for renovation work or for road works, but also for smoothing and profiling rock and concrete walls, Application to fit 3-40tons Excavators & Backhoe Loaders,





dam



Tunnelling work



Cutting face of slope



surface

Digging the foundation for slectric power pylon

Clearing of stumps Soft ground improvement work

Specification

Descriptions		TDC 35	TDC 135	TDC 235	TDC 335	TDC 435
Operating weight	kg	372	845	1,340	1,860	2,620
Input power	kW	25	30	52	60	120
Max. Peak power	kW	34	40	62	70	140
Max. Operating pressure	bar	350	350	350	350	350
Oil flow required	ı /min	30~50	60~90	80~140	140~210	260~400
Cutting speed	rpm	120~200	90~130	65~113	50~90	40~70
Cutting head torque	N.m	3,200	5,800	10,900	24,000	36,000
Cutter diameter	mm	360	460	590	620	730
No. of pick		2X30	2X32	2X36	2X30	2X32
Carrier weight	tons	3.0~8.0	8.0~15.0	15.0~22.0	18.0~30.0	30.0~45.0







Products overview

- ► High cutting force
- ▶ 5 models from 3 to 40 tons base carriers
- ► No required drain line
- ▶ Low maintenance
- ► Low vibration
- ► Low noise



